














Main products







Outside: Facades				Roof	Outside: Wood protection	Outside and inside: Window seal	Inside: Walls and ceilings				
ThermoProtect	History	StuccoTex 80 / 280	StuccoTex Primer	ThermoActive	Nature/ NatureGlaze	NaturePrimer	PU Safe Coating	PU Safe Filler	ThermoPlus	Lumen	ThermoVital
Long-lasting facade protection with energy-saving property	Value-preserving facade protection with gentle dehumidification	Lightweight structural plaster that reduces thermal stresses	Ready-to-use bonding agent for StuccoTex	Reflektierende Dachbeschichtung mit ausgezeichneter Kühlleistung	Coloured and weather-resistant wood protection – opaque / glazing	Ready-to-use adhesion promoter for outdoor wooden components	Efficient protective coating for PU-foam	Filler for PU-foam	Ideal room climate and wide range of colours	Excellent light reflection	Innovative protection against mould
											
Container sizes (l) ↳ 19,00 12,50 5,00	19,00 12,50 5,00	15,00 kg	19,00 12,50 5,00	19,00 12,50 5,00	19,00 5,00 (only Nature) 2,50 0,75	19,00 5,00 2,50 0,75	2,80 1,00	300 ml	19,00 12,50 5,00 2,80	19,00 12,50 5,00	19,00 12,50 5,00
Ø Consumption (ml/m²) with 2 applications ↳ 330	330	1,5 kg/m²	150 (for one-time painting)	600 (with embedding material approx. 1.000)	Nature: 330 / NatureGlaze: 220	150 (with a single coat)	600 m²	k. A.	330	330	330

Further main products, solutions and additional products can be found on page 2. Please refer to the website for technical bulletin and safety data sheets.

... still main products and Services

Outside: Thermal insulation plaster	Outside: Industry	Industry and special solutions
<p>demnächst im Sortiment</p> <p>IsoTex R70 IsoTex E50</p> <p>Lightweight mineral-based thermal insulation and renovation plaster – Grain size up to 2 mm</p> <p>Fine mineral-based thermal insulation plaster – Grain size up to 0,5 mm</p> <p>Versatile coating in industry</p>	<p>Industry-Special</p> <p>There are challenges that do not fit into any category, for example the coating of plastics or textiles. Or it is about special parameters, properties or effects, such as acoustics, material flexibility or catalysis.</p> <p>No matter what problem you are looking for a solution for, just contact us for coatings or related topics.</p> <p>Together, we will find a SpecialSolution for you.</p> 	
  		
<p>Container sizes (l)</p> <p>↳ follows later</p> <p>↳ follows later</p>	<p>19,00</p> <p>12,50</p> <p>5,00</p> <p>2,80</p>	
<p>∅ Consumption depending on the absorbency of the substrate</p> <p>↳ follows later</p> <p>↳ follows later</p>	<p>600</p>	

Additional products

Primers	Finishing	For the systematic removal of mold						
FixPlus	RustPrimer	ZincPrimer	GlossPlus	Sanosil 003	Sanosil 010			
Primer concentrate to adjust the absorbency of mineral substrates	Ready-to-use corrosion protection primer for ferrous metals	Ready-to-use adhesion agent for non-ferrous metals	Clear and glossy protective coating with UV blocker	Surface and aerosol disinfection (Mould spores remover)	Mould prevention (Mould killer)			
								
<p>Gebindegrößen (l)</p> <p>↳ 10,00</p> <p>↳ 5,00</p>	<p>12,00 kg</p>	<p>10,00</p> <p>2,50</p>	<p>10,00</p> <p>5,00</p>	<p>1,00 (carton = 6 bottles)</p>	<p>1,00 (carton = 6 bottles)</p>			
<p>∅ Consumption depending on the absorbency of the substrate</p> <p>↳ 120 ml/m²</p>				<p>140 g/m² at a coat thickness of 50 µm</p>	<p>110 ml/m² at a coat thickness of 20 µm</p>	<p>45 ml/m²</p>	<p>15-30 ml/m³ per room fogging and according to inventory</p>	<p>100 ml/m² per working step</p>

The main products for exterior and interior use and for wood protection can be found on page 1. Please refer to the website for the technical bulletin and safety data sheets.